

LINEAR LIGHT 1.4



/ WITH TRANSPARENT TUBE

23001	LUMILUX-FQ T5 230V 1x24W G5	1 / DRAWING H1
23002	LUMILUX-FQ T5 230V 1x39W G5	2 / DRAWING H2
23003	LUMILUX-FQ T5 230V 1x54W G5	3 / DRAWING H3
23004	LUMILUX-FQ T5 230V 1x49W G5	4 / DRAWING H4
23005	LUMILUX-FQ T5 230V 1x80W G5	4 / DRAWING H4

() / WITH SANDBLASTED (SATIN) TUBE

23006	LUMILUX-FQ T5 230V 1x24W G5	1 / DRAWING H1
23007	LUMILUX-FQ T5 230V 1x39W G5	2 / DRAWING H2
23008	LUMILUX-FQ T5 230V 1x54W G5	3 / DRAWING H3
23009	LUMILUX-FQ T5 230V 1x49W G5	4 / DRAWING H4
23010	LUMILUX-FQ T5 230V 1x80W G5	4 / DRAWING H4

▶ μ
 ▶ μ
 ▶ μ polycarbonate T5 FQ
 μ () μ 70mm
 ▶ μ 1 2 μ Pg11
 μ μ Ip68
 ▶ μ μ μ / μ
 ▶ μ
 ▶ μ μ μ
 ▶ μ μ μ μ

- ▶ Decorative waterproof fitting
- ▶ for indoors and outdoors use
- ▶ suitable for 1 lamp T5 FQ
- ▶ with heavy duty polycarbonate tube transparent or mat (satin)
- ▶ with diameter 70mm
- ▶ with aluminum reflector
- ▶ with 1 or 2 polyamide cable glands Pg11 Ip68
- ▶ with incorporated control gear with electronic ballast
- ▶ suitable for placement on the wall or the ceiling with support base or suspension wire
- ▶ for decorative lighting of building facades, windows, corridors.

