

LINE LIGHT RECESSED 4 FRAMELESS LOUVER


- ▶ Γραμμικό φωτιστικό φθορίου
- ▶ χωνευτό οροφής FRAMELESS
- ▶ εσωτερικού χώρου
- ▶ από χυτό προφίλ αλουμινίου
- ▶ με ανακλαστήρα αλουμινίου με λούβρο
- ▶ κατάλληλο για 2 λυχνίες φθορίου T5 14-80W
- ▶ με ενσωματωμένο ηλεκτρονικό μετασχηματιστή
- ▶ για φωτισμό καταστημάτων, γραφείων, εκθεσιακών χώρων
- ▶ Ceiling linear fluorescent recessed fitting
- ▶ frameless
- ▶ for indoors use
- ▶ from die cast aluminum profile
- ▶ with high lighting performance aluminum reflector with louver
- ▶ suitable for 2 fluorescent lamps T5 14-80W
- ▶ with incorporated electronic transformer
- ▶ suitable for use at shops, offices and showrooms



Κατόπιν παραγγελίας το φωτιστικό μπορεί να παραχθεί και σε μεγαλύτερα μήκη
Upon request the above lighting fitting can be produced in longer lengths



24111	LUMILUX-FH T5 230V 2X14W G5	⬇ ⬆ ⚠	∅ 585mm x 166mm	↗ 587mm x 168mm	↕ 100mm
24112	LUMILUX-FH T5 230V 2X21W G5	⬇ ⬆ ⚠	∅ 885mm x 166mm	↗ 887mm x 168mm	↕ 100mm
24113	LUMILUX-FH T5 230V 2X28W G5	⬇ ⬆ ⚠	∅ 1185mm x 166mm	↗ 1187mm x 168mm	↕ 100mm
24114	LUMILUX-FH T5 230V 2X35W G5	⬇ ⬆ ⚠	∅ 1485mm x 166mm	↗ 1487mm x 168mm	↕ 100mm



24115	LUMILUX-FQ T5 230V 2X24W G5	⬇ ⬆ ⚠	∅ 585mm x 166mm	↗ 587mm x 168mm	↕ 100mm
24116	LUMILUX-FQ T5 230V 2X39W G5	⬇ ⬆ ⚠	∅ 885mm x 166mm	↗ 887mm x 168mm	↕ 100mm
24117	LUMILUX-FQ T5 230V 2X54W G5	⬇ ⬆ ⚠	∅ 1185mm x 166mm	↗ 1187mm x 168mm	↕ 100mm
24118	LUMILUX-FQ T5 230V 2X49W G5	⬇ ⬆ ⚠	∅ 1485mm x 166mm	↗ 1487mm x 168mm	↕ 100mm
24119	LUMILUX-FQ T5 230V 2X80W G5	⬇ ⬆ ⚠	∅ 1485mm x 166mm	↗ 1487mm x 168mm	↕ 100mm

