



LINEAR LIGHT 1.1

ΜΕ ΔΙΑΦΑΝΟ ΣΩΛΗΝΑ / WITH TRANSPARENT TUBE

6429	LUMILUX-FH T5 230V 2x14W G5 ⚡ ⊕ ΣΧΕΔΙΟ A1 / DRAWING A1
6430	LUMILUX-FH T5 230V 2x21W G5 ⚡ ⊕ ΣΧΕΔΙΟ A2 / DRAWING A2
6431	LUMILUX-FH T5 230V 2x28W G5 ⚡ ⊕ ΣΧΕΔΙΟ A3 / DRAWING A3
9601	LUMILUX-FH T5 230V 2x35W G5 ⚡ ⊕ ΣΧΕΔΙΟ A4 / DRAWING A4
8738	LUMILUX-FQ T5 230V 2x49W G5 ⚡ ⊕ ΣΧΕΔΙΟ A4 / DRAWING A4

ΜΕ MAT (ΣΑΤΙΝΕ) ΣΩΛΗΝΑ / WITH SANDBLASTED (SATIN) TUBE

6435	LUMILUX-FH T5 230V 2x14W G5 ⚡ ⊕ ΣΧΕΔΙΟ A1 / DRAWING A1
6436	LUMILUX-FH T5 230V 2x21W G5 ⚡ ⊕ ΣΧΕΔΙΟ A2 / DRAWING A2
6437	LUMILUX-FH T5 230V 2x28W G5 ⚡ ⊕ ΣΧΕΔΙΟ A3 / DRAWING A3
9602	LUMILUX-FH T5 230V 2x35W G5 ⚡ ⊕ ΣΧΕΔΙΟ A4 / DRAWING A4
8740	LUMILUX-FQ T5 230V 2x49W G5 ⚡ ⊕ ΣΧΕΔΙΟ A4 / DRAWING A4


- ▶ Διακοσμητικό φωτιστικό στεγανό
- ▶ για εσωτερικούς και εξωτερικούς χώρους
- ▶ κατάλληλο για μια λυχνία T5 FH ή FQ
- ▶ με σωλήνα polycarbonate διάφανο ή ματ (σατινέ) διαμέτρου Φ70mm
- ▶ με ανακλαστήρα αλουμινίου
- ▶ με 1 ή 2 στιπιοθλίπτες Pg11 από πολυαμίδη IP68
- ▶ με ενσωματωμένο σύστημα έναυσης με ηλεκτρονικό μετ/στη
- ▶ κατάλληλο για τοποθέτηση σε οροφή ή σε τοίχο με ειδικά στηρίγματα ή συρματοσόκιο
- ▶ για αρχιτεκτονικό φωτισμό προσόψεων κτιρίων, παραθύρων, διαδρόμων, πεζόδρομων, γκαράζ.

- ▶ Decorative waterproof fitting
- ▶ for indoors and outdoors use
- ▶ suitable for 1 lamp T5 FH or FQ
- ▶ with heavy duty polycarbonate tube transparent or mat (satin)
- ▶ with diameter Φ70mm
- ▶ with aluminum reflector
- ▶ with 1 or 2 polyamide cable glands Pg11 IP68
- ▶ with incorporated control gear with electronic ballast
- ▶ suitable for placement on the wall or the ceiling with support base or suspension wire
- ▶ for decorative lighting of building facades, windows, corridors,

26


ΣΧΕΔΙΟ A1 / DRAWING A1

CE IP65




ΣΧΕΔΙΟ A2 / DRAWING A2

CE IP65




ΣΧΕΔΙΟ A3 / DRAWING A3

CE IP65



ΣΧΕΔΙΟ A4 / DRAWING A4

CE IP65



01 02 18

Βαμμένα με Πολυεστερική Ηλεκτροστατική Βαφή
Panted with Polyester Electrostatic Powder