













## Simple Round Move cob led



- Σποτ χωνευτό οροφής
  - εσωτερικού χώρου
  - χυτοπρεσαριστό αλουμινίου
  - κινητό ±25°
  - με ενσωματωμένο 1 Cob Led ισχύος
  - ενσωματωμένο σε ψήκτρα υψηλής απόδοσης
  - για την καλύτερη διαχείριση θερμότητας του led
  - CRI>80 | 3 SDCM
  - κατόπιν παραγγελίας με CRI>90 & CRI 98+
  - κατόπιν παραγγελίας με 2 SDCM
  - σε θερμοκρασία χρώματος 2700-3000-4000 Kelvin
  - κατόπιν παραγγελίας και σε 3500-5000-6500 Kelvin
  - με ανακλαστήρα υψηλής απόδοσης
  - με δέσμη 15°-25°-40°-60°
  - λειτουργεί με συνοδευτικό led driver, On/off
  - ή κατόπιν παραγγελίας dimmable
  - phase cut / Dali / 1-10volt
- 
- Recessed ceiling led spotlight
  - for indoors use
  - from die cast aluminum
  - movable ±25°
  - with incorporated 1 Cob Led source
  - adjusted on a high performance heatsink
  - for best thermal management of led source
  - CRI>80 | 3 SDCM as standard
  - upon request available with CRI>90 & CRI 98+
  - upon request available with 2 SDCM
  - in 2700-3000-4000 Kelvin
  - upon request in 3500-5000-6500 Kelvin
  - with high performance reflector
  - available with 15°-25°-40°-60° beam angle
  - works with remote led driver
  - on/off, dimmable phase cut / Dali / 1-10volt


### CRI 80 | Led source power & Average Luminaire Flux

Indicative Flux list | Final lumen output depends from the selection of the angle beam

28380		5.0W   2700-3000-4000 KELVIN   440-460-480 LUMEN	
28381		6.7W   2700-3000-4000 KELVIN   585-615-640 LUMEN	
28382		7.5W   2700-3000-4000 KELVIN   645-675-705 LUMEN	
28383		9.0W   2700-3000-4000 KELVIN   780-820-860 LUMEN	
28384		11.0W   2700-3000-4000 KELVIN   925-965-1000 LUMEN	
28385		12.75W   2700-3000-4000 KELVIN   1050-1100-1150 LUMEN	


∅ 100mm     82mm    ↑ 85-140mm    CE    

### Accessories upon request



Το παραπάνω φωτιστικό προσφέρεται κατόπιν παραγγελίας με μπροστινή προστασία **IP44**

The above luminaire is available upon request with **IP44** front protection



Movable

