

# AXON 160 RD FOCUS 1



- Σποτ led χωνευτό οροφής
- εσωτερικού χώρου
- αλουμινίου
- κινητό ±30°
- με ενσωματωμένο 1 COB LED ισχύος
- τοποθετημένο σε ψήκτρα υψηλής απόδοσης
- για την καλύτερη διαχείρισης θερμότητας του led
- CRI>80 | 3SDCM
- κατόπιν παραγγελίας με CRI>90 & CRI>98+
- κατόπιν παραγγελίας με 2 SDCM
- σε θερμοκρασία χρώματος 2700-3000-4000 Kelvin
- κατόπιν παραγγελίας και σε 3500-5000-6500 Kelvin
- με ανακλαστήρα υψηλής απόδοσης
- με δέσμη 15°-25°-40°-60°
- λειτουργεί με συνοδευτικό led driver on/off
- ή dimmable phase cut / Dali / 1-10volt

- Recessed led spotlight
- for indoors use
- from die cast aluminum
- movable ±30°
- with incorporated 1 Cob Led source
- adjusted on a high performance heatsink
- for best thermal management of the led source
- CRI>80 | 3 SDCM | as standard
- upon request available with CRI>90 & CRI>98+
- upon request available with 2 SDCM
- in 2700-3000-4000 Kelvin
- upon request in 3500-5000-6500 Kelvin
- with high performance reflector
- available with 15°-25°-40°-60° beam angle
- works with remote led driver
- on/off as standard
- upon request dimmable phase cut/Dali/1-10volt

## CRI>80 | Power and Luminous flux

Final lumen output depends on the selection of the angle beam


38627	12.0W	2700-3000-4000 KELVIN	1200-1270-1340 LUMEN	⏏ ⏚
38628	17.5W	2700-3000-4000 KELVIN	1665-1765-1860 LUMEN	⏏ ⏚
38629	21.0W	2700-3000-4000 KELVIN	1960-2080-2190 LUMEN	⏏ ⏚
38630	25.0W	2700-3000-4000 KELVIN	2240-2380-2500 LUMEN	⏏ ⏚
38631	28.0W	2700-3000-4000 KELVIN	2680-2780-2850 LUMEN	⏏ ⏚
38632	32.0W	2700-3000-4000 KELVIN	3025-3150-3265 LUMEN	⏏ ⏚
38633	38.0W	2700-3000-4000 KELVIN	3500-3600-3750 LUMEN	⏏ ⏚
38634	42.0W	2700-3000-4000 KELVIN	4085-4245-4383 LUMEN	⏏ ⏚
38635	50.0W	2700-3000-4000 KELVIN	4785-4975-5142 LUMEN	⏏ ⏚
38636	53.0W	2700-3000-4000 KELVIN	4981-5200-5380 LUMEN	⏏ ⏚

∅ 160mm

145mm

140-180mm

CE IP20



Movable



## Accessories upon request



Smooth light filter 1



Smooth light filter 2



Honey comb louvre

