

















Tube Maxi HQI 1



- Προβολέας εσωτερικού χώρου
- Χυτός αλουμινίου
- βαμμένος με ηλεκτροστατική πούδρα
- με υάλινο προφυλακτήρα tempered
- διάφανο ή ματ πάχους 4mm
- περιστρεφόμενος οριζοντίως 355° και καθέτως ±90°
- κατάλληλος για λυχνίες metal halide 20w-35w-50w-70w
- με ενσωματωμένο ηλεκτρονικό μετασχηματιστή έναυσης
- με ανακλαστήρα αλουμινίου υψηλής απόδοσης
- με δέσμη στενή-μεσαία-ευρεία-πολύ ευρεία
- με ενσωματωμένο τριφασικό adaptor
- διαθέσιμο κατόπιν παραγγελίας
- με βάση αλουμινίου για τοποθέτηση σε οροφή
- διαθέσιμο κατόπιν παραγγελίας
- με multiAdapter με data bus επιλογή

- Track mounted projector
- for indoors use
- from die cast aluminum
- painted with electrostatic powder
- rotatable horizontally 355° and head tiltable 0-90°
- with tempered glass transparent or mat 4mm thick
- suitable for metal halide lamps 20w-35w-50w-70w
- with incorporated electronic metal halide gear
- with high performance aluminum reflector
- available with narrow-medium-wide-extra wide beam
- with incorporated three phase adaptor
- upon request available
- with die cast aluminum base for ceiling mounting
- or with multiAdapter with data bus option

29004		HCI - TC 230V 20W G8.5	
29005		HCI - TC 230V 35W G8.5	
29006		HCI - TC 230V 35W G12	
29007		HQI - T 230V 50W G8.5	
29008		HCI - TC 230V 50W G12	
29009		HQI - T 230V 70W G8.5	
29010		HCI - TC 230V 70W G12	
29011		HQI - TC 230V 70W Rx7s	

Ø150 x 250mm GLASS (4mm) CE IP20

