



- Φωτιστικό led στεγανό χωνευτό επίτοιχο
 - κατάλληλο για χρήση εξωτερικούς χώρους
 - από σώμα και στεφάνι από χυτό αλουμινίου
 - βαμμένα ηλεκτροστατικά με πολυεστερική πούδρα
 - για αντοχή σε καταπονήσεις του εξωτερικού περιβάλλοντος
 - με υάλινο προφυλακτήρα tempered πάχους 4mm
 - με ελαστικά στεγανοποίησης και βίδες inox
 - με ενσωματωμένα linear Smd led modules
 - τοποθετημένα σε γραμμική ψήκτρα
 - για την καλύτερη θερμική διαχείριση
 - CRI>80 | 3 SDCM
 - σε 3000-4000 Kelvin
 - με ενσωματωμένο led driver, on/off
 - ή κατόπιν παραγγελίας διαθέσιμο dimmable
 - phase cut/trailing edge - 1/10v - Dali
 - συνοδεύεται με βάση αλουμινίου για τοποθέτηση στον τοίχο
- Waterproof wall recessed led luminaire
 - suitable for outdoors use
 - from die cast aluminum body and flange
 - polyester powder coated
 - for resistance under harsh environmental conditions
 - with protective tempered glass 4mm thick
 - with waterproof gasket and inox screws
 - with incorporated linear Smd led modules
 - adjusted on a linear heatsink
 - for best thermal management of led source
 - CRI>80 | 3 SDCM as standard
 - available in 3000-4000 Kelvin
 - with built in led driver on/off as standard
 - or upon request available dimmable
 - phase cut/trailing edge - 1/10v - Dali
 - available with aluminum base for wall installation

CRI>80 | Power and Luminous flux

26794  7.0W | 220-240v | 3000-4000 KELVIN | 480-520 LUMEN   

26795  13.8W | 220-240v | 3000-4000 KELVIN | 810-870 LUMEN   

5274 **Κουτί επίτοιχης τοποθέτησης**
Box for wall recessed use

 235x127mm GLASS (4mm)  

