

# Frameless Triple Move Focus 1



- Φωτιστικό τριπλό χωνευτό led σποτ οροφής
  - χωρίς εξωτερικό πλαίσιο
  - frameless/trimless
  - εσωτερικού χώρου
  - αλουμινίου
  - βαμμένο με ηλεκτροστατική βαφή
  - με μπροστινό αντιθαμβωτικό σκίαστρο
  - κινητό οριζοντίως  $\pm 355^\circ$  και καθέτως  $\pm 25^\circ$
  - με ενσωματωμένα 3 cob led
  - ενσωματωμένα σε ψήκτρεις υψηλής απόδοσης
  - για την καλύτερη διαχείριση θερμότητας των led
  - CRI>80 | 3 SDCM
  - κατόπιν παραγγελίας με CRI>90 & CRI 98+
  - σε 2700-3000-4000 Kelvin
  - κατόπιν παραγγελίας και σε 3500-5000-6500 Kelvin
  - με ανακλαστήρες υψηλής απόδοσης
  - με δέσμη  $15^\circ-25^\circ-40^\circ-60^\circ$
  - λειτουργεί με συνοδευτικό led driver
  - On/off ή dimmable phase cut / Dali / 1-10volt
- 
- Recessed triple led spotlight
  - for indoors use
  - frameless/trimless
  - from die cast aluminum
  - painted with electrostatic powder
  - with antiglare hood
  - movable horizontally  $\pm 355^\circ$  and vertically  $\pm 25^\circ$
  - with incorporated 3 cob led sources
  - adjusted on high performance heatsinks
  - for best thermal management of led sources
  - CRI>80 | 3 SDCM as standard
  - upon request available with CRI>90 & CRI 98+
  - upon request available with 2 SDCM
  - in 2700-3000-4000 Kelvin
  - upon request in 3500-5000-6500 Kelvin
  - with high performance reflector
  - available  $15^\circ-25^\circ-40^\circ-60^\circ$  beam angle
  - works with remote led driver
  - On/off, dimmable phase cut/Dali/1-10volt

## CRI>80 | Led source power & Average Luminaire Flux

### Indicative Flux list | Final lumen output depends from the selection of the angle beam

35105	3x5.0W   220-240v   2700-3000-4000 KELVIN   3x(440-460-480) LUMEN	⏏ ⏏ ⏏
35106	3x6.7W   220-240v   2700-3000-4000 KELVIN   3x(585-615-640) LUMEN	⏏ ⏏ ⏏
35107	3x7.5W   220-240v   2700-3000-4000 KELVIN   3x(645-675-705) LUMEN	⏏ ⏏ ⏏
35108	3x9.0W   220-240v   2700-3000-4000 KELVIN   3x(780-820-860) LUMEN	⏏ ⏏ ⏏

Total depth 115mm

Installation depth 100mm



### Accessories upon request




Smooth light filter 1

Smooth light filter 2

Honey comb louvre



Ρυθμιζόμενα πλαινά στηρίγματα για οροφές πάχους από 10mm έως 30mm

Adjustable side brackets for installation onto ceiling with thickness from 10mm up to 30mm



Tiltable

Κινητό οριζοντίως  $\pm 355^\circ$  και καθέτως  $\pm 25^\circ$   
Movable horizontally  $\pm 355^\circ$  and vertically  $\pm 25^\circ$



01 02 18 Βαμμένα με Ηλεκτροστατική Βαφή  
Painted with Electrostatic Powder

Διαθέσιμο και σε άλλα χρώματα κατόπιν παραγγελίας  
Upon request available in different color finishes

\*Η τεχνολογία των LED είναι σε διαρκή εξέλιξη οπότε πριν παραγγείλετε, παρακαλούμε επιβεβαιώστε ποιο LED είναι διαθέσιμο  
LED technology changes constantly forward, so before selecting / ordering the most suitable product for you, ask for a confirmation that this is the most updated product to our list.

■ warm 2700 Kelvin ■ warm white 3000 Kelvin ■ neutral white 4000 Kelvin