

Terra Line Led 4 LLE

Inox | Stainless Steel



- Linear inground recessed waterproof led luminaire
- suitable for outdoors use
- made from extruded anodized aluminum body
- painted with polyester powder suitable for external use
- with protective heavy duty inox (stainless steel) frame
- with ground base from aluminum
- with protective glass 10mm thick mat
- with internal antiglare screen with grilles from aluminum
- with incorporated linear led smd modules
- adjusted on high performance linear heatsink
- for best heat management
- CRI>80 | 3 SDCM as standard
- upon request available with CRI>90
- in 3000-4000 KELVIN
- also available upon request in 2700-3500-5000-6500 Kelvin
- 110° beam angle
- works with built in led driver, on/off as standard
- upon request dimmable phase cut/Dali/1-10v
- with silicone gaskets and stainless-steel screws
- with cable gland PG9 IP68 made from brass
- upon request is available with pre-connected cable
- with 1 cable gland PG9 IP68 made from brass as standard
- or with 2 cable glands PG9 IP68 made from brass
- for input and output of power supply cables
- upon request is available with pre-connected cable

CRI 80 | Led source power & Average Luminaire Flux

Indicative Flux list | Final lumen output depends from the selection of the angle beam

30285	8.8W 220-240v 3000-4000 KELVIN 910-980 LUMEN DIM (1)	⏏ ⏏ ⏏
30286	14W 220-240v 3000-4000 KELVIN 1120-1190 LUMEN DIM (2)	⏏ ⏏ ⏏
30287	21W 220-240v 3000-4000 KELVIN 1680-1785 LUMEN DIM (3)	⏏ ⏏ ⏏
30288	28W 220-240v 3000-4000 KELVIN 2240-2380 LUMEN DIM (4)	⏏ ⏏ ⏏

Linear Led Engine/Module





GLASS (10mm)







ΔΙΑΣΤΑΣΕΙΣ ΦΩΤΙΣΤΙΚΩΝ DIMENSIONS OF LUMINAIRES				ΔΙΑΣΤΑΣΕΙΣ ΒΑΣΕΩΝ ΕΔΑΦΟΥΣ DIMENSIONS OF GROUND BASES		ΔΙΑΣΤΑΣΕΙΣ ΟΠΗΣ OPENING DIMENSIONS		
DIM	CODE	A	B	C	D	LENGTH	WIDTH	DEPTH
1	30285	473mm	319mm	342mm	426mm	439mm	100mm	95mm
2	30286	713mm	615mm	648mm	732mm	745mm	100mm	95mm
3	30287	1113mm	915mm	978mm	1062mm	1075mm	100mm	95mm
4	30288	1313mm	1215mm	1278mm	1362mm	1375mm	100mm	95mm

ΔΙΑΣΤΑΣΕΙΣ ΦΩΤΙΣΤΙΚΟΥ / LUMINAIRE DIMENSIONS



ΔΙΑΣΤΑΣΕΙΣ ΒΑΣΗΣ ΕΔΑΦΟΥΣ / GROUND BASE DIMENSIONS



ΠΡΟΣΟΧΗ: Σε όλα τα φωτιστικά σώματα χωνευτά δαπέδου κατά την εγκατάσταση θα πρέπει να δημιουργείτε τουλάχιστον 20cm βάθος οπής αποστράγγισης, γεμάτη χαλίκι, για την αποφυγή στάσιμων υδάτων ή να χρησιμοποιείτε για τον ίδιο λόγο αγωγούς αποχέτευσης. Χρησιμοποιείτε μόνο καλώδια τύπου H07RN, άλλου είδους καλώδια μπορεί να μην εξασφαλίζουν βαθμό στεγανότητας IP67 ή IP68.

WARNING: In all ground buried lighting fittings installation, at least 20cm depth drain hole filled by gravel must be made to prevent flooding, or for same reason use draining water pipes. Use H07RN cables only as other types of cables may not be conformed to assure the IP67 or IP 68 rating.



5339 IP68 RATED MULTI-WAY CONNECTOR BOX
ΣΤΕΓΑΝΟ ΚΟΥΤΙ ΔΙΑΚΛΑΔΩΣΗΣ

