


Line 50 Dark 5 Smd



- Φωτιστικό led χωνευτό εσωτερικού χώρου
 - κατάλληλο για τοποθέτηση σε οροφή
 - από χυτό προφίλ αλουμινίου
 - ηλεκτροστατικά βαμμένο
 - με ενσωματωμένα High Power Led τεχνολογίας Smd
 - τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
 - για μείωση της θάμβωσης
 - με εσωτερικούς ανακλαστήρες με δέσμη 18°-38°-48°
 - τοποθετημένο σε ψήκτρα υψηλής απόδοσης
 - για την καλύτερη διαχείριση θερμότητας του led
 - CRI>90 | 3 SDCM
 - κατόπιν παραγγελίας με CRI 95+
 - σε θερμοκρασία χρώματος 3000-4000 Kelvin
 - κατόπιν παραγγελίας και σε 2700-3500-5000-6500 Kelvin
 - λειτουργεί με συνοδευτικό led driver, On/off
 - κατόπιν παραγγελίας dimmable phase cut/1-10v/Dali
-
- Ceiling recessed led luminaire
 - suitable for placement onto false ceiling
 - for indoors use
 - from extruded aluminum powder coated
 - with incorporated High Power Led Smd technology
 - adjusted inside a special black anti-glare optical screen
 - suitable for darklight effect
 - with internal reflectors
 - with symmetric angle beam of 18°-38°-48°
 - positioned on a high performance heatsink
 - for best thermal management of led source
 - CRI>90 | 3 SDCM as standard
 - upon request available with CRI 95+
 - in 3000-4000 Kelvin
 - upon request in 2700-3500-5000-6500 Kelvin
 - works with remote/external led driver on/off as standard
 - upon request dimmable phase cut/1-10v/Dali

CRI>90 | System power & Luminous flux

Final lumen output depends on the selection of the angle beam

Beam Angle 18°



35905		7.0W 220-240V 3000-4000 KELVIN 533 - 611 LUMEN		
35906		10.5W 220-240V 3000-4000 KELVIN 766 - 847 LUMEN		
35907		14.0W 220-240V 3000-4000 KELVIN 1026-1132 LUMEN		

Beam Angle 38°



35908		7.0W 220-240V 3000-4000 KELVIN 580 - 635 LUMEN		
35909		10.5W 220-240V 3000-4000 KELVIN 807 - 890 LUMEN		
35910		14.0W 220-240V 3000-4000 KELVIN 1073-1191 LUMEN		

Beam Angle 48°

35911		7.0W 220-240V 3000-4000 KELVIN 570 - 632 LUMEN		
35912		10.5W 220-240V 3000-4000 KELVIN 800 - 875 LUMEN		
35913		14.0W 220-240V 3000-4000 KELVIN 1051-1172 LUMEN		



148mmx50mm 140mmx4 1mm 65mm



Fixed