


Line 50 Dark 15 Smd



- Φωτιστικό led χωνευτό εσωτερικού χώρου
 - κατάλληλο για τοποθέτηση σε οροφή
 - από χυτό προφίλ αλουμινίου
 - ηλεκτροστατικά βαμμένο
 - με ενσωματωμένα High Power Led τεχνολογίας Smd
 - τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
 - για μείωση της θάμβωσης
 - με εσωτερικούς ανακλαστήρες 12°-34°-48°
 - τοποθετημένο σε ψήκτρα υψηλής απόδοσης
 - για την καλύτερη διαχείριση θερμότητας του led
 - CRI>80 | 3 SDCM
 - κατόπιν παραγγελίας με CRI>90 & CRI 98+
 - σε θερμοκρασία χρώματος 3000-4000 Kelvin
 - κατόπιν παραγγελίας και σε 2700-3500-5000-6500 Kelvin
 - λειτουργεί με ενσωματωμένο led driver on/off
 - κατόπιν παραγγελίας dimmable phase cut/1-10v/Dali
-
- Ceiling recessed led luminaire
 - Suitable for placement onto false ceiling
 - for indoors use
 - from extruded aluminum powder coated
 - with incorporated High Power Led Smd technology
 - adjusted inside a special black anti-glare optical screen
 - suitable for darklight effect
 - with internal reflectors
 - with symmetric angle beam of 12°-34°-48°
 - positioned on a high performance heatsink
 - for best thermal management of led source
 - CRI>80 | 3 SDCM as standard
 - upon request available with CRI>90 & CRI 98+
 - upon request available with 2 SDCM
 - in 3000-4000 Kelvin
 - upon request in 2700-3500-5000-6500 Kelvin
 - with built in led driver on/off as standard
 - upon request dimmable phase cut/1-10v/Dali

CRI 80 | Led Source Power & Average Luminaire Flux

Beam Angle 12°

35923		15.0W 15x1.0W 220-240v	3000-4000 KELVIN	1230-1305 LUMEN	
35924		22.5W 15x1.5W 220-240v	3000-4000 KELVIN	1785-1875 LUMEN	
35925		30.0W 15x2.0W 220-240v	3000-4000 KELVIN	2175-2310 LUMEN	


Beam Angle 34°

35926		15.0W 15x1.0W 220-240v	3000-4000 KELVIN	1290-1365 LUMEN	
35927		22.5W 15x1.5W 220-240v	3000-4000 KELVIN	1875-1965 LUMEN	
35928		30.0W 15x2.0W 220-240v	3000-4000 KELVIN	2280-2430 LUMEN	


Beam Angle 48°

35929		15.0W 15x1.0W 220-240v	3000-4000 KELVIN	1350-1425 LUMEN	
35930		22.5W 15x1.5W 220-240v	3000-4000 KELVIN	1965-2070 LUMEN	
35931		30.0W 15x2.0W 220-240v	3000-4000 KELVIN	2400-2550 LUMEN	

413mmx50mm 405mmx41mm 65mm



Fixed



Anti-dazzle Angle



01 02 18

Βαμμένα με Ηλεκτροστατική Βαφή
Painted with Electrostatic Powder

*Η τεχνολογία των LED είναι σε διαρκή εξέλιξη οπότε πριν παραγγείλετε, παρακαλούμε επιβεβαιώστε ποιο LED είναι διαθέσιμο
LED technology changes constantly forward, so before selecting / ordering the most suitable product for you, ask for a confirmation that this is the most updated product to our list.

warm 2700 Kelvin warm white 3000 Kelvin neutral white 4000 Kelvin