

Line 46 Out 1L



- Γραμμικό led φωτιστικό εξωτερικό
 - εσωτερικού χώρου
 - κατάλληλο για τοποθέτηση σε οροφή
 - ή κρεμαστό με kit ανάρτησης*
 - από προφίλ αλουμινίου
 - με πολυκαρμπονικό κάλυμμα ματ οπάλ/σαντινέ
 - με ενσωματωμένο Linear Led Modules
 - CRI80 | 3 SDCM
 - τοποθετημένα σε γραμμική ψήκτρα
 - για καλύτερη διαχείριση της θερμοκρασίας
 - σε θερμοκρασίας χρώματος 3000-4000 Kelvin
 - κατόπιν παραγγελίας και σε 2700-5000-6500 Kelvin
 - κατόπιν παραγγελίας και με CRI>90
 - λειτουργεί με ενσωματωμένο LED driver on/off
 - κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v
 - κατάλληλο για ομοιογενή φωτισμό χωρίς κενά
- Linear Led luminaire
 - surface mounted
 - or pendant with suspension kit*
 - for indoors use
 - from extruded aluminum powder coated
 - with polycarbonate satin opal mat cover
 - with incorporated Linear Led Modules
 - adjusted on a linear cooling system
 - for best heat management
 - CRI>80 | 3 SDCM as standard
 - upon request available with CRI>90
 - CCT 3000-4000 Kelvin
 - upon request also available in 2700-5000-6500 Kelvin
 - works with built in LED driver on/off as standard
 - upon request dimmable phase cut/Dali/1-10v
 - seamless effect without shadows between modules

CRI>80 | Power and luminous flux


CODE	EXTERNAL DIMENSIONS			VERSION 1 LM/W 100		VERSION 2 LM/W 100	
	LENGTH mm	WIDTH mm	HEIGHT mm	POWER WATT	FINAL LUMEN OUTPUT	POWER WATT	FINAL LUMEN OUTPUT
24304	175	46	70	3.1	310	4.3	430
24305	315	46	70	6.2	620	8.6	860
24306	455	46	70	9.3	930	12.9	1290
24307	595	46	70	12.4	1240	17.2	1720
24308	735	46	70	15.5	1550	21.5	2150
24309	875	46	70	18.6	1860	25.8	2580
24310	1015	46	70	21.7	2170	30.1	3010
24311	1155	46	70	24.8	2480	34.4	3440
24312	1295	46	70	27.9	2790	38.7	3870
24313	1435	46	70	31	3100	43	4300
24314	1575	46	70	34.1	3410	47.3	4730
24315	1725	46	70	37.2	3720	51.6	5160
24316	1865	46	70	40.3	4030	55.9	5590
24317	2005	46	70	43.4	4340	60.2	6020
24318	2145	46	70	46.5	4650	64.5	6450
24319	2285	46	70	49.6	4960	68.8	6880
24320	2425	46	70	52.7	5270	73.1	7310
24321	2565	46	70	55.8	5580	77.4	7740
24322	2705	46	70	58.9	5890	81.7	8170
24323	2845	46	70	62	6200	86	8600
24324	2985	46	70	65.1	6510	90.3	9030
24325	3135	46	70	68.2	6820	94.6	9460
24326	3275	46	70	71.3	7130	98.9	9890
24327	3415	46	70	74.4	7440	103.2	10320
24328	3555	46	70	77.5	7750	107.5	10750
24329	3695	46	70	80.6	8060	111.8	11180
24330	3835	46	70	83.7	8370	116.1	11610
24331	3975	46	70	86.8	8680	120.4	12040

Linear Led Module



SUSPENSION KIT

Composed by 2-5 pcs (depending from the length of luminaire) of steel wire with length 1.20m standard length (upon request available in longer lengths) assembled to fitting with all necessary components for ceiling installation, with 1.50m long power supply cable 3x0.75mm transparent- white-black-grey (upon request available in longer lengths), connected to fitting, and 1 pcs of round die cast aluminum ceiling base, painted in same color with luminaire, with external diameter d=60mm and height=15mm.



1. Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4,50m σε ενιαίο σώμα
 Upon request luminaire is offered 4.50m long in one single piece

