


LINE 50 DARK COMB 1




- ▶ Γραμμικό led φωτιστικό χωνευτό οροφής
- ▶ εσωτερικού χώρου
- ▶ από προφίλ αλουμινίου
- ▶ με ενσωματωμένα High Power Led τεχνολογίας Smd
- ▶ τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
- ▶ για μείωση της θάμβωσης
- ▶ με εσωτερικούς ανακλαστήρες 18°-34°-48°
- ▶ με πολυκαρμπονικό κάλυμμα οπάλ/στανιέ
- ▶ και ενσωματωμένα Linear Led Modules
- ▶ κατάλληλα για διάχυτο φωτισμό
- ▶ τοποθετημένα σε γραμμική ψήκτρα
- ▶ για καλύτερη διαχείριση της θερμοκρασίας
- ▶ σε θερμοκρασία χρώματος 3000K - 4000K
- ▶ CRI>80 | 3SDCM
- ▶ λειτουργεί με συνοδευτικό LED driver on/off
- ▶ κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v

- ▶ Recessed false ceiling led luminaire
- ▶ for indoors use
- ▶ from extruded aluminum powder coated
- ▶ with incorporated High Power Led Smd
- ▶ adjusted inside a special black anti-glare optical screen
- ▶ with internal reflectors
- ▶ suitable for darklight effect
- ▶ with symmetric angle beam of 18°-34°-48°
- ▶ with incorporated Linear Led Modules
- ▶ with polycarbonate satin/opal cover
- ▶ suitable for diffuse lighting
- ▶ CRI>80 | 3SDCM as standard
- ▶ positioned on a linear cooling system
- ▶ for best heat management
- ▶ in 3000K or 4000K color temperature
- ▶ works with remote led driver on/off as standard
- ▶ upon request dimmable phase cut/Dali/1-10v



Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4.50m σε ενιαίο σώμα
Upon request the luminaire is offered 4.50m long in one single piece



L1 EXTERNAL DIMENSIONS

CODE	EXTERNAL DIMENSIONS		CUTTING DIMENSIONS			VERSION LM/W 100	
	LENGTH mm	WIDTH mm	LENGTH mm	WIDTH mm	HEIGHT mm	POWER WATT	FINAL LUMEN OUTPUT
39218	312	50	305	40	65	6.2	620
39219	453	50	446	40	65	9.3	930
39220	593	50	586	40	65	12.4	1240
39221	734	50	727	40	65	15.5	1550
39222	874	50	867	40	65	18.6	1860
39223	1015	50	1008	40	65	21.7	2170
39224	1155	50	1148	40	65	24.8	2480
39225	1296	50	1289	40	65	27.9	2790
39226	1436	50	1429	40	65	31	3100
39227	1577	50	1570	40	65	34.1	3410
39228	1717	50	1710	40	65	37.2	3720
39229	1858	50	1851	40	65	40.3	4030
39230	1998	50	1991	40	65	43.4	4340
39231	2139	50	2132	40	65	46.5	4650
39232	2279	50	2272	40	65	49.6	4960
39233	2420	50	2413	40	65	52.7	5270
39234	2560	50	2553	40	65	55.8	5580
39235	2701	50	2694	40	65	58.9	5890
39236	2841	50	2834	40	65	62	6200
39237	2982	50	2975	40	65	65.1	6510
39238	3122	50	3115	40	65	68.2	6820
39239	3263	50	3256	40	65	71.3	7130
39240	3403	50	3396	40	65	74.4	7440
39241	3544	50	3537	40	65	77.5	7750

L2 EXTERNAL DIMENSIONS

CODE	LENGTH mm	NUMBER OF LED SOURCES	POWER WATT	3000K beam angle 12°	4000K beam angle 12°	3000K beam angle 34°	4000K beam angle 34°	3000K beam angle 48°	4000K beam angle 48°
				L2-132-5	132	5	5	410	435
L2-132-7.5	132	5	7.5	595	625	625	655	655	690
L2-132-10	132	5	10	725	770	760	810	800	850
L2-234-10	234	10	10	820	870	860	910	900	950
L2-234-15	234	10	15	1190	1250	1250	1310	1310	1380
L2-234-20	234	10	20	1450	1540	1520	1620	1600	1700
L2-396-15	396	15	15	1230	1305	1290	1365	1350	1425
L2-396-22.5	396	15	22.5	1230	1305	1290	1365	1350	1425
L2-396-30	396	15	30	2175	2310	2280	2430	2400	2550
L2-528-20	528	20	20	2460	2610	2580	2730	2700	2850
L2-528-30	528	20	30	2460	2610	2580	2730	2700	2850
L2-528-40	528	20	40	4350	4620	4560	4860	4800	5100



01 02 18

Βαμμένα με Ηλεκτροστατική Βαφή
Painted with Electrostatic Powder

*Η τεχνολογία των LED είναι σε διαρκή εξέλιξη οπότε πριν παραγγείλετε, παρακαλούμε επιβεβαιώστε πιο LED είναι διαθέσιμο
LED technology changes constantly forward, so before selecting / ordering the most suitable product for you, ask for a confirmation that this is the most updated product to our list.

■ warm 2700 Kelvin ■ warm white 3000 Kelvin ■ neutral white 4000 Kelvin