



LINE 40 DARK COMB 1




- ▶ Γραμμικό led φωτιστικό χωνευτό οροφής
- ▶ εσωτερικού χώρου
- ▶ από προφίλ αλουμινίου
- ▶ με ενσωματωμένα High Power Led τεχνολογίας Smd
- ▶ τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
- ▶ για μείωση της θάμβωσης
- ▶ με εσωτερικούς ανακλαστήρες 12°-34°-48°
- ▶ με πολυκαρμπονικό κάλυμμα οπάλ/στανιέ
- ▶ και ενσωματωμένα Linear Led Modules
- ▶ κατάλληλα για διάχυτο φωτισμό
- ▶ τοποθετημένα σε γραμμική ψήκτρα
- ▶ για καλύτερη διαχείριση της θερμοκρασίας
- ▶ σε θερμοκρασία χρώματος 3000K - 4000K
- ▶ CRI>80 | 3SDCM
- ▶ λειτουργεί με ενσωματωμένο LED driver on/off
- ▶ κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v

- ▶ Recessed false ceiling led luminaire
- ▶ for indoors use
- ▶ from extruded aluminum powder coated
- ▶ with incorporated High Power Led Smd
- ▶ adjusted inside a special black anti-glare optical screen
- ▶ with internal reflectors
- ▶ suitable for darklight effect
- ▶ with symmetric angle beam of 12°-34°-48°
- ▶ with incorporated Linear Led Modules
- ▶ with polycarbonate satin/opal cover
- ▶ suitable for diffuse lighting
- ▶ CRI>80 | 3SDCM as standard
- ▶ positioned on a linear cooling system
- ▶ for best heat management
- ▶ in 3000K or 4000K color temperature
- ▶ works with built in led driver on/off as standard
- ▶ upon request dimmable phase cut/Dali/1-10v



Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4.50m σε ενιαίο σώμα
Upon request the luminaire is offered 4.50m long in one single piece



L1 EXTERNAL DIMENSIONS							
CODE	EXTERNAL DIMENSIONS		CUTTING DIMENSIONS			VERSION LM/W 100	
	LENGTH mm	WIDTH mm	LENGTH mm	WIDTH mm	HEIGHT mm	POWER WATT	FINAL LUMEN OUTPUT
39218	312	40	305	36	80	6.2	620
39219	453	40	446	36	80	9.3	930
39220	593	40	586	36	80	12.4	1240
39221	734	40	727	36	80	15.5	1550
39222	874	40	867	36	80	18.6	1860
39223	1015	40	1008	36	80	21.7	2170
39224	1155	40	1148	36	80	24.8	2480
39225	1296	40	1289	36	80	27.9	2790
39226	1436	40	1429	36	80	31	3100
39227	1577	40	1570	36	80	34.1	3410
39228	1717	40	1710	36	80	37.2	3720
39229	1858	40	1851	36	80	40.3	4030
39230	1998	40	1991	36	80	43.4	4340
39231	2139	40	2132	36	80	46.5	4650
39232	2279	40	2272	36	80	49.6	4960
39233	2420	40	2413	36	80	52.7	5270
39234	2560	40	2553	36	80	55.8	5580
39235	2701	40	2694	36	80	58.9	5890
39236	2841	40	2834	36	80	62	6200
39237	2982	40	2975	36	80	65.1	6510
39238	3123	40	3115	36	80	68.2	6820
39239	3263	40	3256	36	80	71.3	7130
39240	3403	40	3396	36	80	74.4	7440
39241	3544	40	3537	36	80	77.5	7750

L2 EXTERNAL DIMENSIONS									
CODE	LENGTH mm	NUMBER OF LED SOURCES	POWER WATT	3000K beam angle 12°	4000K beam angle 12°	3000K beam angle 34°	4000K beam angle 34°	3000K beam angle 48°	4000K beam angle 48°
				L2-132-5	132	5	5	410	435
L2-132-7.5	132	5	7.5	595	625	625	655	655	690
L2-132-10	132	5	10	725	770	760	810	800	850
L2-234-10	234	10	10	820	870	860	910	900	950
L2-234-15	234	10	15	1190	1250	1250	1310	1310	1380
L2-234-20	234	10	20	1450	1540	1520	1620	1600	1700
L2-396-15	396	15	15	1230	1305	1290	1365	1350	1425
L2-396-22.5	396	15	22.5	1230	1305	1290	1365	1350	1425
L2-396-30	396	15	30	2175	2310	2280	2430	2400	2550
L2-528-20	528	20	20	2460	2610	2580	2730	2700	2850
L2-528-30	528	20	30	2460	2610	2580	2730	2700	2850
L2-528-40	528	20	40	4350	4620	4560	4860	4800	5100

