


## Line 68 Dark Comb 1



- Γραμμικό LED φωτιστικό χωνευτό οροφής
  - εσωτερικού χώρου
  - από προφίλ αλουμινίου
  - με ενσωματωμένα High Power Led τεχνολογίας Smd
  - τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
  - για μείωση της θάμβωσης
  - με εσωτερικούς ανακλαστήρες με δέσμη 18°-38°-48°
  - με πολυκαρπονικό κάλυμμα οπάλ/σατινέ
  - και ενσωματωμένα Linear Led Modules
  - κατάλληλα για διάχυτο φωτισμό
  - τοποθετημένα σε γραμμική ψήκτρα
  - για καλύτερη διαχείριση της θερμοκρασίας
  - σε θερμοκρασία χρώματος 3000K - 4000K
  - CRI>90 | 3SDCM
  - λειτουργεί με ενσωματωμένο LED driver on/off
  - κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v
- Recessed false ceiling led luminaire
  - for indoors use
  - from extruded aluminum powder coated
  - with incorporated High Power Led Smd
  - adjusted inside a special black anti-glare optical screen
  - with internal reflectors
  - suitable for darklight effect
  - with symmetric angle beam of 18°-38°-48°
  - with incorporated Linear Led Modules
  - with polycarbonate satin/opal cover
  - suitable for diffuse lighting
  - CRI>90 | 3SDCM as standard
  - positioned on a linear cooling system
  - for best heat management
  - in 3000K or 4000K color temperature
  - works with built in led driver on/off as standard
  - upon request dimmable phase cut/Dali/1-10v

L1 EXTERNAL DIMENSIONS									
CODE	EXTERNAL DIMENSIONS		CUTTING DIMENSIONS			LUMEN VERSION 1		LUMEN VERSION 2	
	LENGTH mm	WIDTH mm	LENGTH mm	WIDTH mm	HEIGHT mm	POWER WATT	FINAL LUMEN OUTPUT	POWER WATT	FINAL LUMEN OUTPUT
39096	325	68	315	57	70	6.2	620	8.6	860
39097	465	68	455	57	70	9.3	930	12.9	1290
39098	605	68	595	57	70	12.4	1240	17.2	1720
39099	745	68	735	57	70	15.5	1550	21.5	2150
39100	885	68	875	57	70	18.6	1860	25.8	2580
39101	1025	68	1015	57	70	21.7	2170	30.1	3010
39102	1165	68	1155	57	70	24.8	2480	34.4	3440
39103	1305	68	1295	57	70	27.9	2790	38.7	3870
39104	1445	68	1435	57	70	31	3100	43	4300
39105	1585	68	1575	57	70	34.1	3410	47.3	4730
39106	1735	68	1725	57	70	37.2	3720	51.6	5160
39107	1875	68	1865	57	70	40.3	4030	55.9	5590
39108	2015	68	2005	57	70	43.4	4340	60.2	6020
39109	2155	68	2145	57	70	46.5	4650	64.5	6450
39110	2295	68	2285	57	70	49.6	4960	68.8	6880
39111	2435	68	2425	57	70	52.7	5270	73.1	7310
39112	2575	68	2565	57	70	55.8	5580	77.4	7740
39113	2715	68	2705	57	70	58.9	5890	81.7	8170
39114	2855	68	2845	57	70	62	6200	86	8600
39115	2995	68	2985	57	70	65.1	6510	90.3	9030
39116	3145	68	3135	57	70	68.2	6820	94.6	9460
39117	3285	68	3275	57	70	71.3	7130	98.9	9890
39118	3425	68	3415	57	70	74.4	7440	103.2	10320
39119	3656	68	3555	57	70	77.5	7750	107.5	10750

L2 EXTERNAL DIMENSIONS									
CODE	LENGTH mm	NUMBER OF LED SOURCES	POWER WATT	3000	4000	3000	4000	3000	4000
				Beam Angle 18°	Beam Angle 18°	Beam Angle 38°	Beam Angle 38°	Beam Angle 48°	Beam Angle 48°
L2-132-7	132	5	7	533	611	580	635	570	632
L2-132-10.5	132	5	10.5	766	847	807	890	800	875
L2-132-14	132	5	14	1026	1132	1073	1191	1051	1172
L2-234-7	234	10	7	533	611	580	635	570	632
L2-234-10.5	234	10	10.5	766	847	807	890	800	875
L2-234-14	234	10	14	1026	1132	1073	1191	1051	1172
L2-396-7	396	15	7	533	611	580	635	570	632
L2-396-10.5	396	15	10.5	766	847	807	890	800	875
L2-396-14	396	15	14	1026	1132	1073	1191	1051	1172
L2-528-7	528	20	7	533	611	580	635	570	632
L2-528-10.5	528	20	10.5	766	847	807	890	800	875
L2-528-14	528	20	14	1026	1132	1073	1191	1051	1172



**i** Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4.50m σε ενιαίο σώμα  
Upon request the luminaire is offered 4.50m long in one single piece

