

Line Wash 1



CODE	EXTERNAL DIMENSIONS			VERSION 1			VERSION 2		
	LENGTH mm	WIDTH mm	HEIGHT mm	Led source power watt	3000K Luminous Flux	4000K Luminous Flux	Led source power watt	3000K Luminous Flux	4000K Luminous Flux
39547	165	46	90	2.95	299.5	313	4.35	412.5	434
39548	305	46	90	5.9	599	626	8.7	825	868
39549	445	46	90	8.85	898.5	939	13.05	1237.5	1302
39550	585	46	90	11.8	1198	1252	17.4	1650	1736
39551	725	46	90	14.75	1497.5	1565	21.75	2062.5	2170
39552	865	46	90	17.7	1797	1878	26.1	2475	2604
39553	1005	46	90	20.65	2096.5	2191	30.45	2887.5	3038
39554	1145	46	90	23.6	2396	2504	34.8	3300	3472
39555	1285	46	90	26.55	2695.5	2817	39.15	3712.5	3906
39556	1425	46	90	29.5	2995	3130	43.5	4125	4340
39557	1565	46	90	32.45	3294.5	3443	47.85	4537.5	4774
39558	1705	46	90	35.4	3594	3756	52.2	4950	5208
39559	1845	46	90	38.35	3893.5	4069	56.55	5362.5	5642
39560	1985	46	90	41.3	4193	4382	60.9	5775	6076
39561	2125	46	90	44.25	4492.5	4695	65.25	6187.5	6510
39562	2265	46	90	47.2	4792	5008	69.6	6600	6944
39563	2405	46	90	50.15	5091.5	5321	73.95	7012.5	7378
39564	2545	46	90	53.1	5391	5634	78.3	7425	7812
39565	2685	46	90	56.05	5690.5	5947	82.65	7837.5	8246
39566	2825	46	90	59	5990	6260	87	8250	8680
39567	2965	46	90	61.95	6289.5	6573	91.35	8662.5	9114
39568	3105	46	90	64.9	6589	6886	95.7	9075	9548
39569	3245	46	90	67.85	6888.5	7199	100.05	9487.5	9982
39570	3385	46	90	70.8	7188	7512	104.4	9900	10416
39571	3525	46	90	73.75	7487.5	7825	108.75	10312.5	10850
39572	3665	46	90	76.7	7787	8138	113.1	10725	11284
39573	3805	46	90	79.65	8086.5	8451	117.45	11137.5	11718
39574	3945	46	90	82.6	8386	8764	121.8	11550	12152
39575	4085	46	90	85.55	8685.5	9077	126.15	11962.5	12586

Linear Led Module



SUSPENSION KIT

Composed by 2-5 pcs (depending from the length of luminaire) of steel wire with length 1.20m standard length (upon request available in longer lengths) assembled to fitting with all necessary components for ceiling installation, with 1.50m long power supply cable 3x0.75mm transparent-white-black-grey (upon request available in longer lengths), connected to fitting, and 1 pcs of round die cast aluminum ceiling base, painted in same color with luminaire, with external diameter d=60mm and height=15mm.



Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4,50m σε ενιαίο σώμα

Upon request luminaire is offered 4.50m long in one single piece

- Γραμμικό led φωτιστικό εξωτερικό
- εσωτερικού χώρου
- κατάλληλο για τοποθέτηση σε οροφή
- ή κρεμαστό με κιτ ανάρτησης*
- από προφίλ αλουμινίου
- με πολυκαρμπονικό κάλυμμα ματ οπάλ/σατινέ
- κατάλληλο για ασύμμετρο (wall washing effect)
- με ενσωματωμένο Linear Led Modules
- CRI80 | 3 SDCM
- τοποθετημένα σε γραμμική ψήκτρα
- για καλύτερη διαχείριση της θερμοκρασίας
- σε θερμοκρασίας χρώματος 3000-4000 Kelvin
- κατόπιν παραγγελίας και σε 2700-5000-6500 Kelvin
- κατόπιν παραγγελίας και με CRI>90
- λειτουργεί με ενσωματωμένο LED driver on/off
- κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v
- κατάλληλο για ομοιογενή φωτισμό χωρίς κενά
- Linear Led luminaire
- surface mounted
- or pendant with suspension kit*
- for indoors use
- from extruded aluminum powder coated
- with polycarbonate satin opal mat cover
- suitable for wall washing effect
- with asymmetric distribution of light
- with incorporated Linear Led Modules
- adjusted on a linear cooling system
- for best heat management
- CRI>80 | 3 SDCM as standard
- upon request available with CRI>90
- CCT 3000-4000 Kelvin
- upon request also available in 2700-5000-6500 Kelvin
- works with built in LED driver on/off as standard
- upon request dimmable phase cut/Dali/1-10v
- seamless effect without shadows between modules

