

Line Wash 2



CODE	EXTERNAL DIMENSIONS			VERSION 3		
	LENGTH mm	WIDTH mm	HEIGHT mm	Led source power watt	3000K Luminous Flux	4000K Luminous Flux
39576	165	46	90	3.9	389	406.5
39577	305	46	90	7.8	778	813
39578	445	46	90	11.7	1167	1219.5
39579	585	46	90	15.6	1556	1626
39580	725	46	90	19.5	1945	2032.5
39581	865	46	90	23.4	2334	2439
39582	1005	46	90	27.3	2723	2845.5
39583	1145	46	90	31.2	3112	3252
39584	1285	46	90	35.1	3501	3658.5
39585	1425	46	90	39	3890	4065
39586	1565	46	90	42.9	4279	4471.5
39587	1705	46	90	46.8	4668	4878
39588	1845	46	90	50.7	5057	5284.5
39589	1985	46	90	54.6	5446	5691
39590	2125	46	90	58.5	5835	6097.5
39591	2265	46	90	62.4	6224	6504
39592	2405	46	90	66.3	6613	6910.5
39593	2545	46	90	70.2	7002	7317
39594	2685	46	90	74.1	7391	7723.5
39595	2825	46	90	78	7780	8130
39596	2965	46	90	81.9	8169	8536.5
39597	3105	46	90	85.8	8558	8943
39598	3245	46	90	89.7	8947	9349.5
39599	3385	46	90	93.6	9336	9756
39600	3525	46	90	97.5	9725	10162.5
39601	3665	46	90	101.4	10114	10569
39602	3805	46	90	105.3	10503	10975.5
39603	3945	46	90	109.2	10892	11382
39604	4085	46	90	113.1	11281	11788.5

Linear Led Module



CE

IP

SUSPENSION KIT

Composed by 2-5 pcs (depending from the length of luminaire) of steel wire with length 1.20m standard length (upon request available in longer lengths) assembled to fitting with all necessary components for ceiling installation, with 1.50m long power supply cable 3x0.75mm transparent-white-black-grey (upon request available in longer lengths), connected to fitting, and 1 pcs of round die cast aluminum ceiling base, painted in same color with luminaire, with external diameter d=60mm and height=15mm.

Κατόπιν παραγγελίας το φωτιστικό προσφέρεται 4,50m σε ενιαίο σώμα
Upon request luminaire is offered 4.50m long in one single piece

- Γραμμικό led φωτιστικό εξωτερικό
- εσωτερικού χώρου
- κατάλληλο για τοποθέτηση σε οροφή
- ή κρεμαστό με κιτ ανάρτησης*
- από προφίλ αλουμινίου
- με πολυκαρμπονικό κάλυμμα ματ οπάλ/σατινέ
- κατάλληλο για ασύμμετρο (wall washing effect)
- με ενσωματωμένο Linear Led Modules
- CRI80 | 3 SDCM
- τοποθετημένα σε γραμμική ψήκτρα
- για καλύτερη διαχείριση της θερμοκρασίας
- σε θερμοκρασίας χρώματος 3000-4000 Kelvin
- κατόπιν παραγγελίας και σε 2700-5000-6500 Kelvin
- κατόπιν παραγγελίας και με CRI>90
- λειτουργεί με ενσωματωμένο LED driver on/off
- κατόπιν παραγγελίας dimmable phase cut/Dali/1-10v
- κατάλληλο για ομοιογενή φωτισμό χωρίς κενά
- Linear Led luminaire
- surface mounted
- or pendant with suspension kit*
- for indoors use
- from extruded aluminum powder coated
- with polycarbonate satin opal mat cover
- suitable for wall washing effect
- with asymmetric distribution of light
- with incorporated Linear Led Modules
- adjusted on a linear cooling system
- for best heat management
- CRI>80 | 3 SDCM as standard
- upon request available with CRI>90
- CCT 3000-4000 Kelvin
- upon request also available in 2700-5000-6500 Kelvin
- works with built in LED driver on/off as standard
- upon request dimmable phase cut/Dali/1-10v
- seamless effect without shadows between modules

