

Line 5 Dark CL



- Φωτιστικό led εσωτερικού χώρου
 - κατάλληλο για τοποθέτηση σε οροφή
 - από χυτό προφίλ αλουμινίου
 - ηλεκτροστατικά βαμμένο
 - με ενσωματωμένα High Power Led τεχνολογίας Smd
 - τοποθετημένα σε ειδικό οπτικό, βαμμένο σε μαύρο χρώμα
 - για μείωση της θάμβωσης
 - με εσωτερικούς ανακλαστήρες με δέσμη 18°-38°-48°
 - τοποθετημένο σε ψήκτρα υψηλής απόδοσης
 - για την καλύτερη διαχείριση θερμότητας του led
 - CRI>90 | 3 SDCM
 - κατόπιν παραγγελίας με CRI 95+
 - σε θερμοκρασία χρώματος 3000-4000 Kelvin
 - κατόπιν παραγγελίας και σε 2700-3500-5000-6500 Kelvin
 - λειτουργεί με ενσωματωμένο led driver on/off
 - κατόπιν παραγγελίας dimmable phase cut/1-10v/Dali
- Ceiling mounted led luminaire
 - for indoors use
 - from extruded aluminum powder coated
 - with incorporated High Power Led Smd technology
 - adjusted inside a special black anti-glare optical screen
 - suitable for darklight effect
 - with internal reflectors
 - with symmetric angle beam of 18°-38°-48°
 - positioned on a high performance heatsink
 - for best thermal management of led source
 - CRI>90 | 3 SDCM as standard
 - upon request available with CRI 95+
 - in 3000-4000 Kelvin
 - upon request in 2700-3500-5000-6500 Kelvin
 - with built in led driver on/of as standard
 - upon request dimmable phase cut/1-10v/Dali

CRI>90 | System power & Luminous flux



Beam Angle 18°

25655  7.0W | 220-240V | 3000-4000 KELVIN | 533 - 611 LUMEN 25656  10.5W | 220-240V | 3000-4000 KELVIN | 766 - 847 LUMEN 25657  14.0W | 220-240V | 3000-4000 KELVIN | 1026-1132 LUMEN 

Beam Angle 38°

25658  7.0W | 220-240V | 3000-4000 KELVIN | 580 - 635 LUMEN 25659  10.5W | 220-240V | 3000-4000 KELVIN | 807 - 890 LUMEN 25660  14.0W | 220-240V | 3000-4000 KELVIN | 1073-1191 LUMEN 

Beam Angle 48°

25661  7.0W | 220-240V | 3000-4000 KELVIN | 570 - 632 LUMEN 25662  10.5W | 220-240V | 3000-4000 KELVIN | 800 - 875 LUMEN 25663  14.0W | 220-240V | 3000-4000 KELVIN | 1051-1172 LUMEN  137mmx36.5mm 86mmCE 

Fixed

