
Technoline Slim 5



- ➤ Linear led lighting fitting
- > wall fixed mounted
- > waterproof suitable for exteriors use
- > from extruded aluminum polyester powder coated
- > suitable for resistance in external spaces
- with incorporated High Power Led Smd technology
- > CRI>80 | 3 SDCM |as standard
- > upon request available with CRI>90
- > adjusted on a linear cooling system for best thermal management
- in 3000-4000 Kelvin
- ➤ upon request also available in 2700-3500-5000-6500K
- ➤ with symmetric lenses 10°-15°-25°-35°-45°-60°*
- > or elliptical beam lenses 15°x35°, 20x60°*
- > or wall washing lenses
- works with built in led driver, on/off as standard
- > upon request available with dimmable led driver
- > phase cut/Dali/1-10volt
- with 1 cable gland IP68
- with brackets at the two sides for capability of movement
- with silicon gaskets and inox screws

* due to wide variety of available and suitable lenses for above luminaire, the included angle beams are indicative and can be considered as the most used. Upon request the beam angle of the lenses can be adjusted accordingly to your needs.



Final lumen output depends on the selection of the angle beam

23898

5.85W |220-240V | 3000 - 4000 KELVIN | 555 - 595 LUMEN

23899



8.75 W |220-240V | 3000 - 4000 KELVIN | 775 - 835 LUMEN






58x48mm
























Καρφωτά στηρίγματα εδάφους διαθέσιμα κατόπιν παραγγελίας

Ground spikes available upon request



Καρφί ΡVC

PVC spike 5083



Καρφί αλουμινίου Die cast aluminum spike

5019

200mm

Καρφί inox Inox ground spike

5018













*Η τεχνολογία των LED είναι σε διαρκή εξέλιξη οπότε πριν παραγγείλετε, παρακαλούμε επιβεβαιώστε ποιο LED είναι διαθέσιμο $\textbf{LED technology changes constantly forward, so before selecting} \, / \, ordering \, the \, most \, suitable \, product \, for \, you, \, described by the constant of the contraction of the$ ask for a confirmation that this is the most updated product to our list.