

## SPACE MIN TRACK LED



- Προβολέας led εσωτερικού χώρου
- κατάλληλος για τοποθέτηση σε ράγα
- χυτός αλουμινίου
- βαμμένος με ηλεκτροστατική πούδρα
- περιστρεφόμενος οριζοντίως 355° και καθέτως ±90°
- με ενσωματωμένο 1 COB LED ισχύος
- τοποθετημένο σε ψήκτρα υψηλής απόδοσης
- για την καλύτερη διαχείριση θερμότητας του led
- CRI>80 | 3 SDCM
- κατόπιν παραγγελίας με CRI>90 & CRI>95+
- κατόπιν παραγγελίας με 2 SDCM
- σε θερμοκρασία χρώματος 2700-3000-4000 Kelvin
- κατόπιν παραγγελίας και σε 3500-5000-6500 Kelvin
- με ανακλαστήρα υψηλής απόδοσης ή φακό
- με δέσμη 15°-25°-40°
- με ενσωματωμένο led driver on/of

- Indoor track mounted led spotlight
- from die cast aluminum
- painted with electrostatic powder
- rotatable horizontally 355° and head tiltable ± 90°
- with incorporated 1 COB LED
- adjusted on a high performance heatsink
- for best thermal management of led source
- CRI>80 | 3SDCM as standard
- upon request available with CRI>90 & CRI>95+
- upon request available with 2 SDCM
- in 2700-3000-4000 Kelvin
- upon request in 3500-5000-6500 Kelvin
- with high performance reflector or lens
- available with 15°-25°-40° beam angle
- with build in on/off led driver as standard

### CRI>80 | Led source power and Luminous flux

Final lumen output depends on the selection of the angle beam

29713	7.5W	220-240v	2700-3000-4000 KELVIN	638-675-713 LUMEN	⏏ ⏏ ⏏
29714	9.0W	220-240v	2700-3000-4000 KELVIN	765-810-855 LUMEN	⏏ ⏏ ⏏
29715	11.0W	220-240v	2700-3000-4000 KELVIN	935-990-1045 LUMEN	⏏ ⏏ ⏏

∅ 85mm

↕ 168mm

CE IP20

### Accessories upon request




Smooth light filter 1



Smooth light filter 2



Honey comb louvre



Κινητό οριζοντίως ±355°  
και καθέτως ±90°  
Movable horizontally ±355°  
and vertically ±90°

