

Faretti 1 ALU

Led Version



- Χωνευτό επίτοιχο φωτιστικό Led
 - στεγανό κατάλληλο για χρήση σε εξωτερικούς χώρους
 - κατάλληλο για συμμετρικό φωτισμό
 - με δέσμη 96.5°
 - από χυτό αλουμίνιο
 - βαμμένο ηλεκτροστατικά με πολυεστερική πούδρα
 - για αντοχή σε σκληρές περιβαλλοντικές συνθήκες
 - με προστατευτικό υάλινο tempered προφυλακτήρα mat
 - με ενσωματωμένα power smd led
 - CRI>80
 - διαθέσιμο σε 3000-4000 Kelvin
 - κατόπιν παραγγελίας διατίθεται σε 2700 Kelvin
 - με ενσωματωμένο led driver on/off
 - με ελαστικά στεγανοποίησης σιλικόνης και βίδες inox
 - συνοδεύεται από βάση τοποθέτησης στον τοίχο αλουμινίου
 - κατάλληλο για τοποθέτηση σε κήπους, βεράντες, σκαλοπάτια και διαδρόμους
- Wall recessed led luminaire
 - waterproof, suitable for exteriors use
 - suitable for symmetrical lighting effect
 - with 96.5° beam angle
 - made from die-cast aluminum
 - electrostatic polyester powder coated
 - for resistance under harsh environmental conditions
 - with protective tempered glass
 - with incorporated power SMD Led
 - CRI>80
 - in 3000-4000 Kelvin
 - upon request available in 2700 Kelvin
 - with built in led driver on/off
 - with silicone rubber gaskets and stainless-steel screws
 - with aluminum wall base for wall installation
 - suitable for lighting of gardens, walkways, corridors and stairs

CRI>80 | Power and luminous flux

27572  6.0W | 220-240 V | 3000-4000 KELVIN | 310-330 LUMEN  

27573  8.5W | 220-240 V | 3000-4000 KELVIN | 415-445 LUMEN  

∅ 115mm  110mm  80mm GLASS (4mm)  CE  IP65

