

# Gemini RD 100 Extra Wide



- > Φωτιστικό led χωνευτό οροφής
  - > εσωτερικού χώρου
  - > αλουμινίου
  - > σταθερό
  - > με υάλινο προφυλακτήρα tempered διάφανο
  - > ή ματ/οπάλ κατόπιν παραγγελίας
  - > με ενσωματωμένο 1 COB LED ισχύος
  - > τοποθετημένο σε ψήκτρα υψηλής απόδοσης
  - > για την καλύτερη διαχείριση θερμότητας του led
  - > CRI>80 | 3 SDCM
  - > κατόπιν παραγγελίας με CRI>90 & CRI >95+
  - > σε θερμοκρασία χρώματος 2700-3000-4000 Kelvin
  - > κατόπιν παραγγελίας και σε 3500-5000-6500 Kelvin
  - > με ανακλαστήρα αλουμινίου υψηλής απόδοσης
  - > με δέσμη 81°
  - > λειτουργεί με συνοδευτικό led driver
  - > on/off ή dimmable phase cut / Dali / 1-10volt
- 
- > Recessed luminaire
  - > for indoors use
  - > from die cast aluminum
  - > fixed
  - > with tempered glass transparent as standard
  - > upon request opal/mat
  - > with incorporated 1 cob led source
  - > adjusted on a high performance heatsink
  - > for best thermal management of the led source
  - > CRI>80 | 3 SDCM
  - > upon request, available with CRI>90 & CRI 95+
  - > in 2700-3000-4000 Kelvin
  - > upon request in 3500-5000-6500 Kelvin
  - > with high performance aluminum reflector
  - > available with 81° beam angle
  - > works with remote led driver
  - > On/off, dimmable phase cut/Dali/1-10volt

## CRI>80 | Power and Luminous flux



40638		6.10W   2700-3000-4000 KELVIN   604-636-664 LUMEN	HEIGHT: 95mm		
40639		7.40W   2700-3000-4000 KELVIN   668-703-733 LUMEN	HEIGHT: 95mm		
40640		8.20W   2700-3000-4000 KELVIN   733-772-804 LUMEN	HEIGHT: 95mm		
40641		10.4W   2700-3000-4000 KELVIN   892-939-980 LUMEN	HEIGHT: 95mm		
40642		12.6W   2700-3000-4000 KELVIN   1046-1100-1148 LUMEN	HEIGHT: 115mm		
40643		14.8W   2700-3000-4000 KELVIN   1194-1257-1310 LUMEN	HEIGHT: 115mm		

100mm


82mm

95-115mm

CE IP23 FRONT



FIXED



IP44 IP54

### Accessories upon request



Honey comb louvre



Smooth Filter



Elliptical Filter

Το παραπάνω φωτιστικό προσφέρεται κατόπιν παραγγελίας με μπροστινή προστασία IP44 - IP54

The above luminaire is available upon request with IP44 - IP54 front protection

