

Luce 1.1 External Led



- Φωτιστικό led εξωτερικό στεγανό επίτοιχο
- κατάλληλο για χρήση σε εξωτερικούς χώρους
- σώμα και στεφάνι από χυτό αλουμίνιο
- βαμμένα ηλεκτροστατικά με πολυεστερική πούδρα
- για αντοχή σε καταπονήσεις του εξωτερικού περιβάλλοντος
- με υάλινο προφυλακτήρα tempered πάχους 4mm
- με ελαστικά στεγανοποίησης και βίδες inox
- με ενσωματωμένα power led smd
- τοποθετημένα σε γραμμική ψύκτρα
- για την καλύτερη θερμική διαχείριση
- CRI>80 | 3 SDCM
- κατόπιν παραγγελίας με CRI>90
- 3000-4000 Kelvin
- κατόπιν παραγγελίας διαθέσιμο σε 2700-5000-6500 Kelvin
- με ενσωματωμένο led driver , on/off
- ή κατόπιν παραγγελίας διαθέσιμο dimmable

- Waterproof external wall surface led luminaire
- suitable for outdoors use
- from die cast aluminum body
- and die cast aluminum flange
- painted with polyester electrostatic powder
- for resistance under harsh environmental conditions
- with protective tempered glass 4mm thick
- with waterproof gasket and inox screws
- with incorporated power led smd technology
- adjusted on a linear heatsink
- for best thermal management of led source
- CRI>80 | 3 SDCM
- upon request with CRI>90
- available in 3000-4000 Kelvin
- upon request, available in 2700-5000-6500 Kelvin
- with built in led driver on/off as standard
- or upon request available dimmable

CRI>80 | Led source power & Luminous flux

37394	4.6W 220-240v	2700-3000 - 4000 KELVIN	195-207-210 LUMEN	⚡ ⚠ ⚡
37395	6.2W 220-240v	2700-3000 - 4000 KELVIN	258-275-279 LUMEN	⚡ ⚠ ⚡
37396	9.1W 220-240v	2700-3000 - 4000 KELVIN	325-346-351 LUMEN	⚡ ⚠ ⚡

240x105mm GLASS (4mm) CE IP65

