


## Luce 1.4 Led



- Φωτιστικό led στεγανό χωνευτό επίτοιχο
- κατάλληλο για χρήση εξωτερικούς χώρους
- από σώμα χυτό αλουμινίου
- και στεφάνι χυτό αλουμινίου με προστατευτικές ίσιες γρίλιες
- βαμμένα ηλεκτροστατικά με πολυεστερική πούδρα
- για αντοχή σε καταπονήσεις του εξωτερικού περιβάλλοντος
- με υάλινο προφυλακτήρα tempered πάχους 4mm
- με ελαστικά στεγανοποίησης και βίδες inox
- με ενσωματωμένα power led smd
- τοποθετημένα σε γραμμική ψύκτρα
- για την καλύτερη θερμική διαχείριση
- CRI>80 | 3 SDCM
- κατόπιν παραγγελίας με CRI>90
- 3000-4000 Kelvin
- κατόπιν παραγγελίας διαθέσιμο σε 2700-5000-6500 Kelvin
- με ενσωματωμένο led driver, on/off
- ή κατόπιν παραγγελίας διαθέσιμο dimmable
- συνοδεύεται με βάση αλουμινίου για τοποθέτηση στον τοίχο

- Waterproof wall recessed led luminaire
- suitable for outdoors use
- from die cast aluminum body
- and die cast aluminum flange with protective grilles
- painted with polyester electrostatic powder
- for resistance under harsh environmental conditions
- with protective tempered glass 4mm thick
- with waterproof gasket and inox screws
- with incorporated power led smd technology
- adjusted on a linear heatsink
- for best thermal management of led source
- CRI>80 | 3 SDCM
- upon request with CRI>90
- available in 3000-4000 Kelvin
- upon request, available in 2700-5000-6500 Kelvin
- with built in led driver on/off as standard
- or upon request available dimmable
- available with aluminum base for wall installation

### CRI>80 | Led source power and luminous flux

37388	4.6W   220-240v   2700- 3000 - 4000 KELVIN   55-58-59 LUMEN	⚡ ⚙ ⚠
37389	6.2W   220-240v   2700- 3000 - 4000 KELVIN   73-78-79 LUMEN	⚡ ⚙ ⚠
37390	9.1W   220-240v   2700- 3000 - 4000 KELVIN   92-97-99 LUMEN	⚡ ⚙ ⚠

### 5270 Κουτί επίτοιχης τοποθέτησης από αλουμίνιο Box for wall installation from aluminum

