



## Terra Line Led 10 Asymmetric




- Linear inground recessed waterproof led luminaire suitable for outdoors use
- made from extruded anodized aluminum body
- painted with polyester powder suitable for external use
- with ground base from aluminum
- with heavy duty protective glass 8mm thick
- with incorporated high power led smd
- adjusted on high performance linear heatsink for best heat management
- CRI>80 | 3 SDCM as standard
- upon request available with CRI>90
- In 3000 - 4000 KELVIN
- also available upon request in 2700-3500-5000-6500 Kelvin
- with lenses of asymmetrical beam angle
- works with built in led driver, on/off as standard
- upon request dimmable phase cut/Dali/1-10v
- with silicone gaskets and stainless-steel screws
- with 1 or 2 brass nickel plated cable glands IP68
- for input and output of power supply cables
- offered with pre-fitted neoprene cable
- with male and female fis fast connection with IP68 protection

## CRI&gt;80 | Power &amp; Luminous Flux

30719	14.0W   7x2.0W   220-240V   3000-4000 KELVIN   1179-1270 LUMEN   DIM (1)	⚠ ⚠ ⚠
30720	28.0W   14x2.0W   220-240V   3000-4000 KELVIN   2358-2540 LUMEN   DIM (2)	⚠ ⚠ ⚠
30721	42.0W   21x2.0W   220-240V   3000-4000 KELVIN   3537-3810 LUMEN   DIM (3)	⚠ ⚠ ⚠
30722	56.0W   28x2.0W   220-240V   3000-4000 KELVIN   4716-5080 LUMEN   DIM (4)	⚠ ⚠ ⚠

GLASS (8mm)


CE IP67




ΔΙΑΣΤΑΣΕΙΣ ΦΩΤΙΣΤΙΚΩΝ DIMENSIONS OF LUMINAIRES				ΔΙΑΣΤΑΣΕΙΣ ΒΑΣΕΩΝ ΕΔΑΦΟΥΣ DIMENSIONS OF GROUND BASES		ΔΙΑΣΤΑΣΕΙΣ ΟΠΗΣ OPENING DIMENSIONS		
DIM	CODE	A	B	C	D	LENGTH	WIDTH	DEPTH
1	30719	406mm	315mm	391mm	406mm	419mm	80mm	125mm
2	30720	702mm	611mm	687mm	702mm	715mm	80mm	125mm
3	30721	1002mm	911mm	987mm	1002mm	1015mm	80mm	125mm
4	30722	1302mm	1211mm	1287mm	1302mm	1315mm	80mm	125mm

**i** \*upon request available at length 1545mm



## ΔΙΑΣΤΑΣΕΙΣ ΦΩΤΙΣΤΙΚΟΥ / LUMINAIRE DIMENSIONS



## ΔΙΑΣΤΑΣΕΙΣ ΒΑΣΗΣ ΕΔΑΦΟΥΣ / GROUND BASE DIMENSIONS



With pre-connected IP68  
male and female fis for fast connection



**ΠΡΟΣΟΧΗ:** Σε όλα τα φωτιστικά σώματα χωνευτά δαπέδου κατά την εγκατάσταση θα πρέπει να δημιουργείτε τουλάχιστον 20cm βάθος οπής αποστράγγισης, γεμάτη χαλίκι, για την αποφυγή στάσιμων υδάτων ή να χρησιμοποιείτε για τον ίδιο λόγο αγωγούς αποχέτευσης. Χρησιμοποιείτε μόνο καλώδια τύπου H07RN, άλλου είδους καλώδια μπορεί να μην εξασφαλίζουν βαθμό στεγανότητας IP67 ή IP68.

**WARNING:** In all ground buried lighting fittings installation, at least 20cm depth drain hole filled by gravel must be made to prevent flooding, or for same reason use draining water pipes. Use H07RN cables only as other types of cables may not be conformed to assure the IP67 or IP 68 rating.



5339 IP68 RATED MULTI-WAY CONNECTOR BOX  
ΣΤΕΓΑΝΟ ΚΟΥΤΙ ΔΙΑΚΛΑΔΩΣΗΣ

